

INNOVATION - SERVICE - EXPERIENCE

LIQUID GYPSUM TECHNICAL GRADE



AQUA-GYP



ANALYSIS	w/v%	w/v%
Calcium (as calcium sulphate)	17.4	Sulphur (as sulphate) 14.0

SHAKE OR STIR WELL BEFORE USE.

COMPATIBILITY:
AQUA-GYP should **NOT** be applied with any other nutrients or chemicals.

SAFETY DIRECTIONS:
Avoid contact with skin and eyes and avoid breathing in vapour or spray mist.

CONDITIONS OF SALE:
The Manufacturer warrants that this nutrient liquid gypsum product contains the active constituents, as specified, and it is for the purpose of supplying the appropriate major nutrient or correcting soil salinity when used in accordance with directions under normal conditions of use. No one, other than the officer of the Manufacturer, is authorised to make any warranty, guarantee or direction concerning the product as the time, place, rate of application and other conditions are beyond the control of the Manufacturer.

CONTACT:
Tech Support: 0407 040 820 | info@sjbagnutri.com.au | www.sjbagnutri.com.au

Australian Owned & Manufactured by SJB AG~NUTRI PTY. LTD.

©2024

APPLICATION RATES:

Sodium % (ESP)	Sand/Loam (L/ha)	Clay (L/ha)	General in crop rate
5.0-7.5	25-60	60-85	10-20 L/ha monthly
7.5-10	60-85	85-110	
10-15	85-110	110-135	
>15	110-135	135-160	

RECOMMENDATIONS:

AQUA-GYP should be applied with a minimum dilution of 1 part product to 10 parts water and kept agitated to minimise any settlement. If fertigating with dripper flow rates of 2 L/hr or less, we recommend a maximum rate of 10 L/ha & up to 20-30 L/ha with 4 L/hr drippers. Lines should be flushed thoroughly after AQUA-GYP application or before fertigating other products.

Batch No.	Contents	20L	200L	1000L

